

5

10

1

REFORMATTING A DOCUMENT USING FUZZY MATCHING

15 Technical Field

The present invention relates to reformatting a document using a desktop word processing or publishing application program module. More particularly, the present invention relates to automatically reformatting each discrete portion of a document with a format from a format set that is determined to most closely match the existing format of the document.

Background of the Invention

Desktop word processing and publishing application programs allow laymen users to create professional-looking documents and other output. Many prior art application programs provide tools that allow a user to custom format a document. For example, tools may be provided for selecting font face, font size, font color, text alignment, and other formatting options. Such tools are typically independent of one another, which forces the user to individually select and apply different formatting options until a desirable look for the document is discovered.

In order to tie some of the formatting options together, some application programs allow the user to define "styles." To define a style, the user is able to interact with various menus and controls in order to custom format a portion of text. The user may then name the custom format and cause the custom format name

to appear in a "styles menu" or the like. Subsequent text may be selected and automatically formatted with the custom format by interacting with the styles menu. Style tools, however, tend to go undiscovered by the typical layman user. When discovered, style tools tend to be confusing to the typical user. In particular, many users have a difficult time modifying the style tags that they have created.

In addition to the difficulties encountered with formatting tools, laymen users generally lack the training and experience needed to create professional-looking documents from scratch. For example, laymen users are typically not trained to know which fonts look best in which sizes and in which color schemes. Also, many times laymen users do not know, in advance of creating a document, what formats they desire for the document. Laymen users are, however, able to compare several differently formatted documents to determine which style is most suitable to them.

Accordingly, some prior art application programs offer "templates," which provide the layman user with a constrained range of formatting choices, and thus well defined starting points for creating professional-looking documents. A template is a predefined format definition that is usually tied to a theme. For example, an application program may provide a birthday template for creating birthday cards or invitations, a garage sale template for creating garage sale signage, and the like. For the more creative layman user, templates tend to be too rigid and unyielding. While it may be possible to modify the format definitions within a template, it is often tedious and difficult to do so.

Thus, there remains a need for an application program to provide a simple and integrated tool for formatting a document according to a constrained range of formatting choices. There is a further need for simple and integrated tool for formatting a document according to a constrained range of formatting choices that is not tied to a predetermined theme.

Summary of the Invention

The present invention satisfies the above described needs by providing a single integrated formatting tool, referred to as a format gallery. The format gallery provides a constrained range of formatting choices by way of formats within a format set. A format comprises a format font name, a format font size, a format font color,

and other formatting options. A format set is defined by a color set and a font set. A color set comprises a plurality of colors defining a color scheme. The colors of the color scheme are pre-selected by a trained document designer. The font set comprises a plurality of fonts defining a font theme, each font having a font name and a font size. Again, the fonts of the font theme are predefined by a trained document designer based on their aesthetic appeal in relation to each other. The format gallery of the present invention allows the user to preview and select both a color set and a font set.

Once a format set is determined, the present invention employs a “fuzzy matching” method for reformatting the document. According to the fuzzy matching method, each discrete portion of text in the document is analyzed to determine a text font name, a text font, color and a text font size. Then, for each format in the format set, it is determined if the format font name matches the text font name. If the format font name does match the text font name, a first number of points is added to a match quality value associated with the format. Then it is determined if the format font color matches the text font color. If the format font color does match the text font color, a second number of points is added to the match quality value associated with the format. It is next determined if the format font size is greater than the text font size. If so, the ratio of the text font size to the format font size is multiplied by a third number to determine a first product and the first product is added to the match quality value. If the format font size is not greater than the text font size, the ratio of the format font size to the text font size is multiplied by the third number to determine a second product and the second product is added to the match quality value. For the rest of the applicable properties, the algorithm of the fuzzy matching method can be applied. That is, if a property matches that of the format, then a product is added to the quality match value for that format. When a final match quality value is determined for each format in the format set, the format having the greatest associated match quality value is applied to the discrete portion of text.

Brief Description of the Drawings

FIG. 1, comprising FIG. 1A and FIG. 1B, illustrates an exemplary interface of a word processing program module incorporating an exemplary integrated formatting tool of the present invention.

FIG. 2 illustrates an exemplary live preview interface of an exemplary integrated formatting tool of the present invention.

FIG. 3 is a functional block diagram of a computer system that may serve as an exemplary operating environment for implementation of the program modules of the present invention.

FIG. 4 is a flow chart illustrating an exemplary fuzzy matching method for reformatting a document in accordance with an embodiment of the present invention.

FIG. 5 is a flow chart illustrating an exemplary live preview method for reformatting document text in accordance with an embodiment of the present invention.

Detailed Description of the Exemplary Embodiments

The inventive concept relates to a method and system for automatically reformatting a previously created document. It is assumed herein that all previously created documents are formatted with at least a default format. Thus, an act of formatting a previously created document may also be considered to be an act of reformatting the document. Accordingly, the term “reformat” and variations thereof may herein be used interchangeably with the term “format” and variations thereof.

Rather than providing templates having rigid design styles, the present invention provides a number of “format sets.” A format set is made up of a number of formats. Each format is characterized by a font name (font face), font color, font size, etc. Formats are predetermined by a skilled document designer, who is trained to know which font faces work well in various color schemes and font sizes. In addition, the designer is trained to know what colors work well together in various types of documents.

According to the one aspect of the invention, a format set is defined by a font set and a color set. A font set comprises a number of fonts which tend to work well within a given theme. By way of illustration, a font set labeled “hefty” may include heavier fonts and other fonts that work well with the heavier fonts. The “hefty” font set may comprise various sizes of the font *Rockwell Extra Bold* and the font *Lucida Sans*. A color set comprises a number of colors that, in the trained opinion of the designer, may be used to create a document having a professional-

looking color scheme. For example, a color set labeled “grape” may comprise several colors representing various shades and hues of the color purple. Thus, given a font set and a color set, a format set comprises a select combination of fonts, font sizes and colors.

5 One or more tools (user interfaces) may be provided for allowing the user to select from among a number of available font sets and color sets. In an exemplary embodiment, a single tool allows the user to select both a color set and a font set. Once the color set and font set are selected, the corresponding format set may be determined. As mentioned, a format set comprises a number of predefined
10 formats (i.e., format_N , format_{N+1} , format_{N+2} , ...). Each format is predefined by a trained document designer based on aesthetic appeal. A sample of various formats included in the selected format set may be displayed to the user, so that the user can decide if the selected format set is desirable. Once the user decides on a format set, an input command may be entered to cause the selected format set to be applied to the
15 document.

Application of the format set to the document is done in such a way that the integrity and proportionality of the document are maintained. For example, the document may include a title that is displayed in a first font face having a first size. The document may also include section headings that are displayed in a second
20 font face having a second size. The body text of the document may be of a third font face and size. Accordingly, when the document is reformatted, the invention will attempt to maintain aesthetic differences between the font faces of the title, section headings, and body text, respectively. In addition, the invention will attempt to reformat the document so as to maintain a close approximation of the original
25 proportionality between the title, section headings, and body text sizes, respectively.

Exemplary embodiments of the present invention will hereinafter be described with reference to the drawings, in which like numerals represent like elements throughout the several figures. FIG. 1, comprising FIG. 1A and FIG. 1B, is a screen shot of the interface of a word processing program module that illustrates an
30 exemplary integrated formatting tool of the present invention. The integrated formatting tool of the present invention is referred to herein as a “format gallery” 102. Referring first to FIG. 1A, the format gallery 102 is a single user interface that allows the user to select both a font set 104 and a color set 106. A sliding scale user interface

control, referred to herein as a “font slider” **105**, is provided in order to allow the user to browse through each of the available font sets. Similarly, a sliding scale user interface control, referred to herein as a “color slider” **107**, is provided in order to allow the user to browse through all of the available color sets.

5 As mentioned, the selection of a font set **104** and a color set **106** determines the format set. The format gallery **102** may also include a preview window **108**, which displays a color sample **110** and text sample **112** for the selected format set. The color sample **110** includes the various colors included in the selected color set **106**. The text sample **112** includes several portions of text that are formatted
10 in various sizes, colors and fonts according to the selected format set.

The format gallery **102** may be displayed as a floating window that hovers above the document **114** that is to be formatted or reformatted. The document **114** shown in FIG. 1A is a sample newsletter that has previously been formatted. As may be seen, the title **116** is displayed in a first font face and a first font size; the
15 section headings **118a, b** are displayed in the first font size and a second font size; and the body text **120** is displayed in a second font face and a third font size. Although not discernable from the figure, the title **116**, section headings **118a, b**, and body text **120** may each be displayed in a different color.

After a font set **104** and a color set **106** are selected via the format
20 gallery **102** to define a format set, an input command may be generated to initiate the process of applying the selected format set to the document **114**. The input command may be generated by way of an “Apply all” button **122**, or similar control interface. According to one aspect of the invention, reformatting of the document **114** is performed in such a way as to maintain its integrity and proportionality.
25 Reformatting is performed according to a method referred to herein as “fuzzy matching.”

Prior to turning to FIG. 1B, assume that the document **114** of FIG. 1A has the following formats: the title **116** is displayed in a forty-eight point *NewZurica* font face having an orange color; the section headings **118a, b** are each displayed in
30 an eighteen point *Times New Roman* font face with a red color; and the body text **120** is displayed in a twelve point *Arial* font face having an automatic (black) color. Also note that the format gallery **102** indicates that the selected font set **104** is “*Curly-Q*” and the selected color set **106** is “*Ocean*.” Thus, the selected format set is referred to

as “*Curly-Q Ocean*.” FIG. 1A thus portrays the state of the document **114** prior to activation of the “Apply all” button **122**.

FIG. 1B shows the reformatted document **114'** after the *Curly-Q Ocean* format set was selected and the “Apply all” button **122** was activated. The reformatted title **116'** is now displayed in a forty-eight point *Curlz MT* font face having a midnight teal color; the reformatted section headings **118a', b'** are each displayed in a twenty-two point *Curlz MT* font face with a green color; and the reformatted body text **120'** is displayed in a twelve point *Tempus Sands ITC* font face having an automatic (black) color. Accordingly, the selected *Curly-Q Ocean* format set was applied to the document **114** in such a manner that the integrity and proportionality of the original formatting were largely maintained. In particular, the relative size differences between the title **116**, the section headings **118a, b**, and the body text **120** were closely maintained. Also, although the original colors of the title **116**, and the section headings **118a, b** were altered, color variations between the title **116**, the section headings **118a, b**, and the body text **120** were maintained within the predefined *Ocean* color scheme.

As mentioned, one aspect of the invention contemplates application of a format set according to a fuzzy matching method. According to the fuzzy matching method, a document **114** includes one or more originally formatted portions of text. The originally formatted portions of text are each analyzed to identify the original formatting thereof. Then, the original formatting of each portion of text is compared to each format included within the selected format set. The format of the format set that most closely matches the original formatting of each portion of text is applied to the corresponding portion of text. In order to determine whether an original formatting most closely matches a format within a format set, a weighted ranking or other appropriate logic operation may be employed. As an example of the fuzzy matching method, in reformatting the document **114** of FIG. 1, a determination may be made as to which of the formats included within the *Curly-Q Ocean* format set most closely matched the original format (*NewZurica*, forty-eight point, orange) of the title **116**. Some of the predetermined formats included in the *Curly-Q Ocean* format set are: (*Curlz MT*, forty-eight point, midnight teal), (*Curlz MT*, twenty-six point, medium green), (*Curlz MT*, twenty-two point, green), (*Curlz MT*, fourteen point, midnight teal), (*Curlz MT*, seventeen point, green), (*Tempus Sans ITC*, twelve

point, automatic), (*Curlz MT*, eleven point, midnight teal), (*Tempus Sans ITC*, ten point, automatic), (*Tempus Sans ITC*, ten point, medium green), (*Tempus Sans ITC*, ten point, turquoise) and (*Tempus Sans ITC*, nine point, green). It may be seen that none of the above-listed formats from the *Curly-Q Ocean* format set define a font color of orange or a font face of *NewZurica* and only one format defines a font size of forty-eight points. Thus, a weighting ranking based on matching font color, font face and font size may lead to the conclusion that the format (*Curlz MT*, forty-eight point, midnight teal) from the *Curly-Q Ocean* format set most closely matches the original format (*NewZurica*, forty-eight point, orange) of the title **116**. Accordingly, the reformatted title **116'** shown in FIG. 1B is displayed in a forty-eight point *Curlz MT* font having a color of midnight teal. Further details regarding exemplary embodiments of the fuzzy matching method will be described below.

FIG. 2 is a screen shot of the interface of a word processing program module that illustrates an exemplary “live preview” aspect of the format gallery **102** of the present invention. The phrase “live preview” is used herein to describe a method of demonstrating the appearance of a portion of text formatted with several different formats. In one embodiment, live preview allows the user to view and compare a selected portion of text, referred to as the live preview text **201**, in several formats at the same time. Thus, the user is able to visualize the appearance of the live preview text **201** in different formats, before actually selecting a format for reformatting the text in the document **114**.

As shown in FIG. 2, a “format item” tab **202** or other appropriate interface control may be provided for the format gallery **102**. Activation of the format item tab **202** triggers a second display of the format gallery **102**. The second display of the format gallery **102** is geared toward reformatting an individual item (e.g., portion of text) in a document **114**. The second display of the format gallery **102** thus differs in function from the first display, shown in and described with respect to FIG. 1, which is geared toward reformatting the entire document **114**. The second display of the format gallery **102** includes a control, such as a pull-down menu, for selection of a font set **104**. The second display of the format gallery **102** also includes a control, such as a pull-down menu, for selection of a color set **106**. Furthermore, the second display of the format gallery **102** includes a live preview window **204** for

displaying live preview text **201** in various formats from a format set defined by the selected color set **104** and the selected font set **106**.

A format sample may be determined from the format set. A format sample comprises a number of formats from the format set. The live preview text will be displayed in the live preview window **204** in each of the formats from the format sample. As shown, the live preview text **201** comprising the words “Sed Diam” is displayed in several sample formats. A format sample may be used for live preview because the number of formats within an entire format set may be too large. The formats within the format sample may thus be representative formats from the format set that should provide the user with several aesthetically pleasing design choices. Accordingly, from a given format set, a different format sample may be chosen for live preview of title text **116** than would be chosen for live preview of body text **120**. A format sample chosen for live preview of title text **116** may include heavier fonts, larger font sizes, and bolder font colors, for example.

In one embodiment, choice of the live preview text **201** may depend on whether the user has selected any text within the document **114** for live preview. Thus, the document **114** may be scanned to determine whether the user has highlighted a portion of text, so as to indicate a desire to live preview the highlighted text. In another embodiment, the live preview text **201** may be considered to be the text positioned immediately adjacent to the cursor (even if no highlighting is detected). As demonstrated in FIG. 2, the first line of the section heading **118a** “Sed Diam” is positioned immediately adjacent to the cursor **207** and is thus displayed as the live preview text **201**. In any case, if no text within the document **114** can be identified for live preview, a default text string, such as the word “text” may be used as the live preview text **201**. Depending on the size of the live preview window **204**, the live preview text **201** may be constrained to a particular number of characters. In particular, if the cursor **207** is positioned at the start of the first sentence of the body text **120**, it may be the case that only the first few words “Ipsum dolor sit” are used for live preview.

The second display of the format gallery **102** may also include a “custom format window” **206**. By way of the custom format window **206**, the user may be provided the opportunity to create a custom format to be added to the sample of formats and to the format set. By way of illustration, the user may interact with

any of the formatting tools provided by the application program in order to apply a certain format to a portion of text. The user may then select the custom formatted portion of text, such as by highlighting or positioning the cursor in proximity thereto. Once selected, the custom formatted portion of text will be displayed as the live preview text **201** in the live preview window **204** (reformatted according to a sample of formats.) However, if the user activates an appropriate control, such as an “add” button **208**, the custom formatted portion of text may be displayed (with the custom format) in the custom format window **206**. The custom format may also be added to the sample of formats and to the format set. Thus, subsequent live preview text **201** will be displayed with the appropriate sample of formats in the live preview window **204** and with the custom format in the custom format window **206**. Those skilled in the art will appreciate that the custom format window **206** may be implemented as a portion of the live preview window **204** or as its own separate window.

After the live preview text **201** is displayed in the live preview window **204** and/or the custom format window **206**, the user may select one of the sample or custom formats, for example, by interacting with the desired portion of live preview text **201** with a pointing device. Selection of one of the sample or custom formats causes the corresponding text within the document **114** to be reformatted accordingly.

The exemplary embodiments of the present invention may be implemented by way of one or more program modules comprising computer-executable instructions for performing the methods of the present invention. Generally, program modules include routines, programs, components, data structures, etc. that perform particular tasks or implement particular abstract data types when executed by a computer system. FIG. 3 is a block diagram of a computer system that may serve as an exemplary operating environment for implementation of the program modules of the present invention. The exemplary operating environment includes a general-purpose computing device in the form of a conventional personal computer **320**.

Generally, a personal computer **320** includes a processing unit **321**, a system memory **322**, and a system bus **323** that couples various system components including the system memory **322** to processing unit **321**. System bus **323** may be any of several types of bus structures including a memory bus or memory controller, a peripheral bus, and a local bus using any of a variety of bus architectures. The system

memory includes a read only memory (ROM) **324** and random access memory (RAM) **325**. A basic input/output system (BIOS) **326**, containing the basic routines that helps to transfer information between elements within personal computer **320**, such as during start-up, is stored in ROM **324**.

5 Personal computer **320** further includes a hard disk drive **327** for reading from and writing to a hard disk, not shown, a magnetic disk drive **328** for reading from or writing to a removable magnetic disk **329**, and an optical disk drive **330** for reading from or writing to a removable optical disk **331** such as a CD-ROM or other optical media. Hard disk drive **327**, magnetic disk drive **328**, and
 10 optical disk drive **330** are connected to system bus **323** by a hard disk drive interface **332**, a magnetic disk drive interface **333**, and an optical disk drive interface **334**, respectively. Although the exemplary environment described herein employs hard disk **327**, removable magnetic disk **329**, and removable optical disk **331**, it should be appreciated by those skilled in the art that other types of
 15 computer readable media which can store data that is accessible by a computer, such as magnetic cassettes, flash memory cards, digital video disks, Bernoulli cartridges, RAMs, ROMs, and the like, may also be used in the exemplary operating environment. The drives and their associated computer readable media provide nonvolatile storage of computer-executable instructions, data structures, program
 20 modules, and other data for personal computer **320**. For example, one or more data files **360** may be stored in the RAM **325** and/or hard drive **327** of the personal computer **320**.

 A number of program modules may be stored on hard disk **327**, magnetic disk **329**, optical disk **331**, ROM **324**, or RAM **325**, including an operating
 25 system **335**, one or more application program modules **336**, a fuzzy matching module **338**, a live preview program module **339**, and other program modules. The fuzzy matching module **338** and the live preview program module **339** of the present invention may be incorporated into or may otherwise be in communication with the application program module **336**. Generally, a fuzzy matching module **338** includes
 30 computer-executable instructions for analyzing a target document to identify discrete portions of text and determining which formats of a selected format set are to be applied to each identified discrete portion of text. A live preview program module **339** generally comprises computer-executable instructions for applying a number of

different formats from a format set to a sample of text and displaying the samples of formatted text.

A user may enter commands and information into personal computer **320** through input devices, such as a keyboard **340** and a pointing device **342**. Other input devices (not shown) may include a microphone, joystick, game pad, satellite dish, scanner, or the like. These and other input devices are often connected to processing unit **322** through a serial port interface **346** that is coupled to the system bus **323**, but may be connected by other interfaces, such as a parallel port, game port, a universal serial bus (USB), or the like. A display device **347** may also be connected to system bus **323** via an interface, such as a video adapter **348**. In addition to the monitor, personal computers typically include other peripheral output devices (not shown), such as speakers and printers.

Personal computer **320** may operate in a networked environment using logical connections to one or more remote computers **349**. Remote computer **349** may be another personal computer, a server, a client, a router, a network PC, a peer device, or other common network node. While a remote computer **349** typically includes many or all of the elements described above relative to personal computer **320**, only a memory storage device **350** has been illustrated in the figure. The logical connections depicted in the figure include a local area network (LAN) **351** and a wide area network (WAN) **352**. Such networking environments are commonplace in offices, enterprise-wide computer networks, intranets, and the Internet.

When used in a LAN networking environment, personal computer **320** is connected to local area network **351** through a network interface or adapter **353**. When used in a WAN networking environment, personal computer **320** typically includes a modem **354** or other means for establishing communications over WAN **352**, such as the Internet. Modem **354**, which may be internal or external, is connected to system bus **323** via serial port interface **346**. In a networked environment, program modules depicted relative to personal computer **320**, or portions thereof, may be stored in the remote memory storage device **350**. It will be appreciated that the network connections shown are exemplary and other means of establishing a communications link between the computers may be used.

Moreover, those skilled in the art will appreciate that the present invention may be implemented in other computer system configurations, including

hand-held devices, multiprocessor systems, microprocessor based or programmable consumer electronics, network person computers*, minicomputers, mainframe computers, and the like. The invention may also be practiced in distributed computing environments, where tasks are performed by remote processing devices that are linked through a communications network. In a distributed computing environment, program modules may be located in both local and remote memory storage devices.

FIG. 4 is a flow chart illustrating an exemplary fuzzy matching method in accordance with one embodiment of the present invention. The exemplary method **400** begins at starting block **401**, where an application program module, such as a word processing or desktop publishing program module, is executed by a computer system. From starting block **401**, the method proceeds to step **402**, where a format set is determined based on user selection of a color set and a font set. Next, the method **400** moves to step **404**, where each format in the format set is determined. As previously mentioned, a format set may include a number of predefined formats (format_n, format_{n+1}, format_{n+2}, ...). In an exemplary embodiment, a format defines a font face, a font size and a font color. Those skilled in the art will appreciate that a format may also define any other formatting option, such as font style (bold, italics, etc), text alignment, list styles (bullets, numbering, etc.), and the like.

At step **406**, a document is scanned to identify and select the next (first) a discrete portion of text. As used herein, the term "discrete portion of text" is meant to describe a continuous portion of text having a consistent format applied thereto. A document may thus comprise one or more discrete portions of text. Thus, the text of a document may be scanned in order to locate transitions in formatting, which would signify a new discrete portion of text. Those skilled in the art will appreciate that there may be many alternate methods for scanning text to identify discrete portions thereof.

Next at step **408**, the first discrete portion of document text is analyzed to determine its font name, font color, font size. Again, for the sake of simplification, this example discusses only font name, font color and font size, although other format properties may be utilized as well. At step **410**, the first format in the format set is selected. For clarity, the format of the format set may be referred to herein in terms of format_font name, format_font color and format_font size, while the original format

of the document text may be referred to herein in terms of text_font name, text_font color and text_font size.

At step **412**, a determination is made as to whether the format_font name matches the text_font name. If the format_font name matches the text_font name, a determined number of “points” is added to a “match quality value” at step **414**. A match quality value is a value that is recorded for each format of the format set and used for subsequent comparison purposes. Thus, a match quality value_n is calculated for each format_n of the format set. Match quality values are thus relative values, meaning that their starting values and number of points added to match quality values are discretionary. For example, each initial match quality value may be zero and five points may be added to the initial match quality value if the format_font name matches the text_font name.

If the format_font name does not match the text_font name at step **412**, or after the appropriate number of points are added to the match quality value at step **414**, the method proceeds to step **416**, where a determination is made as to whether the format_font color matches the text_font color. If the format_font color matches the text_font color, another determined number of points is added to the match quality value at step **418**. The determined number of points may be the same as or different from the number of points added for a font name match. Obviously a different number of points would be added for a font color match if it were desired to weight such a match differently.

If the format_font color does not match the text_font color at step **416**, or after the appropriate number of points are added to the match quality value at step **418**, the method proceeds to step **420**, where a determination is made as to whether the format_font size is greater than the text_font size. If the format_font size is greater than the text_font size, the method moves to step **422**. At step **422**, the ratio of the text_font size to the format_font size is multiplied by a determined number X (e.g., X=30) and that number of points is added to the match quality value. Again, the determined number is discretionary based on the weight desired to be assigned to a font size match. If the format_font size is not greater than the text_font size the method proceeds to step **424**. At step **424**, the ratio of the format_font size to the text_font size is multiplied by the determined number X and that number of points is

added to the match quality value. After the appropriate number of points are added to the match quality value at step **422** or step **424**, the method proceeds to step **426**.

The above-described weighting process is repeated for every format in the format set. Thus, at step **426**, a determination is made as to whether there is another format in the format set. If so, n is incremented ($n = n+1$) at step **428** such that the next format and corresponding match quality value are selected. From step **428**, the above-described method is repeated from step **412** until it is determined at step **426** that there is no other format in the format set. When it is determined that there is no other format in the format set, the method advances to step **430**, where the format having the greatest match quality value is applied to the selected discrete portion of text in the document. Then at step **432**, a determination is made as to whether there is another discrete portion of text in the document. If so, n is reset ($n=1$) at step **434** and the above-described method is repeated from step **406** until it is determined that there is not other discrete portion of document text at step **432**. When it is determined that there is no other discrete portion of document text to be reformatted, the method ends at step **436**. Therefore, by way of the above-described fuzzy matching method, each discrete portion of text in a document may be reformatted with a different format from the selected format set. As a result, the integrity and proportionality of the document should be largely preserved.

FIG. 5 is a flow chart illustrating an exemplary live preview method **500** in accordance with an exemplary embodiment of the present invention. The method **500** begins at starting block **501**, where an application program module, such as a word processing or desktop publishing program module, is executed by a computer system. From starting block **501**, the method **500** proceeds to step **502**, where a format set is determined based on user selection of a color set and a font set. Next at step **504**, a sample of formats is determined from the format set. A sample of formats comprises some or all of the formats in the format set. Thus, the sample of formats comprises format_N , format_{N+1} , format_{N+2} , ... A selected string of text will be displayed in each of the formats included within the sample of formats. As such, the sample of formats should include a enough representative formats to give the user a wide range of format choices within a format set

At step **506**, the live preview text is identified. In one embodiment, the document may be scanned in order to determine what text, if any, has been selected

by the user for live preview. For example, it may be determined that the user has highlighted a portion of text indicating a desire to live preview the highlighted text. In another the text positioned immediately adjacent to the cursor may be considered to be the live preview text. In any case, if no live preview text can be identified, a
 5 default text string, such as the word “text” may be used as the live preview text. Depending on the size of the live preview pane, the live preview text may be constrained to a particular number of characters.

As mentioned, the live preview text will be displayed in each of the formats included within the sample of formats. Thus, at step **508**, the first format
 10 from the sample of formats is selected. As mentioned, a format may comprise many properties, such as font name, font color and font size. At step **510** the live preview text is reformatted with the selected sample and at step **512** the reformatted text is displayed in a preview pane. Then at step **514**, a determination is made as to whether there is another format in the sample of formats. If another format exists, the next
 15 format is chosen ($N = N + 1$) and the method returns to step **510**, where the live preview text is reformatted with the selects format. The method is thus repeated from step **510** until it is determined at step **514** that no other formats exist within the sample of formats. It should be appreciated that display of the live preview text in each of the formats of the sample of formats may be accomplished in various ways,
 20 such as in a list or table. However, it is preferable to display all (or at least some) of the differently formatted text at the same time, so that the user may compare the different appearances.

In one embodiment, the user may be provided the opportunity to create a custom format to be added to the sample of formats and to the format set. For
 25 example, the user may apply a certain format to a portion of text and then select that portion of text as the live preview text. The user may then activate an “add” button or other suitable interface in order to cause the existing format of the live preview text to be added to the sample of formats and to the format set. Accordingly, subsequent live preview text will be displayed in the custom format as well as the other formats
 30 included in the sample of formats. Optionally, within the live preview pane, live preview text formatted with a custom format may be separated from live preview text formatted with standard formats. When it is determined that there are no other formats in the sample of formats, the method **500** ends at step **516**.

The above description of exemplary embodiment of the present invention were provided by way of example only and not by way of limitation. Many elements of exemplary embodiments have been described using permissive language, such as "may" or "should," meaning that such elements are optional and not mandatory. Unless an element has been described using clear mandatory language, such as "must" or "shall," it should be considered an optional element. From a reading of the foregoing, alternate embodiments of the present invention will become apparent to those having ordinary skill in the art to which the present invention pertains. Such alternate embodiments are considered to be encompassed within the spirit and scope of the present invention. Accordingly, the scope of the present invention is described by the appended claims and is supported by the foregoing description.